



NOTES:

- CENTERLINE OF MOUNTING HOLE OF UPPER AND LOWER RETAINERS ALIGNED 0 DEG
- DO NOT INFLATE TO MORE THAN 6.9 BAR WITHOUT GOODYEAR APPROVAL.
- FASTENER TORQUE NOT TO EXCEED 27 N-m.
- ASSEMBLY TO BE SUPPORTED, TOP AND BOTTOM, BY MINIMUM 108mm DIAMETER PLATE. EXTERNAL LIMITS MUST BE PROVIDED IN MOUNTING STRUCTURE TO PREVENT SPRING FROM EXCEEDING MIN AND MAX HEIGHTS.

5			
4	STEEL CLAMP RING	ASB-08-4-024	2
3	UPPER RETAINER	ASC-92-8-281	1
2	LOWER RETAINER	ASB-92-6-082	1
1	FLEXIBLE MEMBER	579-91-3-510	1

ITEM	NAME	DRAWING NO./SPEC. NO	REQ.
BILL OF MATERIALS			

▽ INDICATES A KEY CRITICAL CHARACTERISTIC (KCC), WHICH MUST CONFORM TO GMS VI-010

THE GOODYEAR TIRE & RUBBER COMPANY GREEN, OHIO

THIS DRAWING AND THE ASSOCIATED TAPING INSTRUCTIONS ARE THE PROPERTY OF THE GOODYEAR TIRE & RUBBER COMPANY. ALL RIGHTS ARE RESERVED. NO PART OF THIS DRAWING OR TAPING INSTRUCTIONS MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT PERMISSION IN WRITING FROM THE GOODYEAR TIRE & RUBBER COMPANY. APPROVED FOR RELEASE TO THE PUBLIC BY THE GOODYEAR TIRE & RUBBER COMPANY. THIS DRAWING IS THE PROPERTY OF THE GOODYEAR TIRE & RUBBER COMPANY. ALL RIGHTS ARE RESERVED. NO PART OF THIS DRAWING OR TAPING INSTRUCTIONS MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT PERMISSION IN WRITING FROM THE GOODYEAR TIRE & RUBBER COMPANY.

DESIGN BY: KM BUCHANAN 10/15/96

DATE: 10/15/96

DEPT NO: 021

SCALE: 1:1

11th 1B6-833 METRIC ASSEMBLY

579-91-2-833

FO21-000.R01 ASSY FRAME-C

TOLERANCE ON FINISHED SURFACES,
UNLESS OTHERWISE SHOWN:

mm	INCH
X .0	.XX ± .030
X .007	.XXX ± .010
X .010	.XXX ± .010

ANGLES ± 0.0°

FINISHES -

NOTE: DRAWING MAY NOT BE
PLOTTED TO SCALE

9	REV. NO.	
8	REV. NO.	
5	REV. NO.	
4	REV. NO.	
2	REV. NO.	
3	REV. NO.	

1. DIM. 3.0/0.0524
2. MIN. TO METAL HEIGHT MAX
4mm, ADJUSTED TO 5mm.